



MATERIAL SPECIFICATIONS **INDEX™ WOOD WT**

Materials:

Natural Wood Fibers (including Curlex® Fibers)
High Grade Organic Tackifier
Green Dye

Description:

Index Wood WT is a hydraulically applied mulch that provides an organic cover to protect seeds, enhance germination, and hasten re-vegetation when mixed with water and applied with hydraulic mulching equipment. Index Wood WT is a blend of natural wood fibers (including Curlex Fibers), high grade organic tackifier, and green dye. Index Wood WT is available palletized in bags for applicator convenience. Index Wood WT shall be manufactured in the U.S.A.

Index Wood WT has a design soil loss ratio (event-based RUSLE C factor) of ≤ 0.15 and is typically suitable for slopes up to 3H:1V. Index Wood WT improves germination by $\geq 200\%$ (ASTM D 7322).

Physical Properties:

| | |
|-------------------------|--|
| Fiber: | Natural Wood Fibers |
| Fiber Length: | 25% or more of fibers ≥ 0.40 in (10.2 mm) long 50% of fibers retained on #24 sieve |
| Bag Gross Weight: | ≈ 50.0 lb (22.7 kg) |
| Green Dye: | ≈ 8.0 oz (0.227 kg) |
| Tackifier: | ≈ 24.0 oz (0.68 kg) |
| Bag Volume: | 10.0 ft ³ (283 L) Before Compression 3.9 ft ³ (110 L) After Compression |
| Moisture Content: | 12% \pm 3% |
| pH: | 7.3 (ASTM D 778) |
| Organic Matter: | 98.25% (ASTM D 2974) |
| Ash Content: | 1.72% (ASTM D 2974) |
| Water Holding Capacity: | 1,042% (ASTM D 7367) |

All measurements are based on product at time of manufacture.





MANUFACTURER'S CERTIFICATION
BINDEX™ WOOD WT – Hydraulic Mulch

Provider:

American Excelsior Company
831 Pioneer Avenue
Rice Lake, WI 54868
1-866-9FIBERS (1-866-934-2377)

Project Information (if applicable):

Name:

Location:

Number:

Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

| | |
|-------------------------|---|
| Composition: | Natural Wood Fibers (including Curlex® Fibers), High Grade Organic Tackifier, Green Dye |
| Fiber Length: | 25% or more of fibers ≥ 0.40 in (10.2 mm) long 50% of fibers retained on #24 sieve |
| Bag Gross Weight: | ≈ 50.0 lb (22.7 kg) |
| Green Dye: | ≈ 8.0 oz (0.227 kg) |
| Tackifier: | ≈ 24.0 oz (0.68 kg) |
| Bag Volume: | 10.0 ft³ (283 L) Before Compression 3.9 ft³ (110 L) After Compression |
| Moisture Content: | 12% ± 3% |
| pH: | 7.3 (ASTM D 778) |
| Organic Matter: | 98.25% (ASTM D 2974) |
| Ash Content: | 1.72% (ASTM D 2974) |
| Water Holding Capacity: | 1,042% (ASTM D 7367) |

All measurements are based on product at time of manufacture.

TJ 4.4

Tony Johnson – General Manager, Rice Lake

Effective Date

Note: This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacturer's Certifications (MSMC) for AEC products shall be accessed from www.Curlex.com at all times.

