Proud Participant in NTPEP and Proud Member of:

Product Participant of:



## Earth Science Division <u>MATERIAL SPECIFICATIONS</u> CURLEX<sup>®</sup> NetFree<sup>™</sup>

## Materials:

Great Lakes Aspen (naturally seed free) Biodegradable Stitching Thread

### **Typical Roll Sizes:**

American Excelsior

Company<sup>®</sup>

Width:	8.0 ft (2.4 m)
Length:	90.0 ft (27.4 m)
Area:	$80.0 \text{ yd}^2 (66.9 \text{ m}^2)$
Weight:	58.4 lb (26.5 kg)

### **Description:**

Curlex NetFree erosion control blanket (ECB) is a 100% biodegradable, stitched excelsior blanket that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. Curlex NetFree is furnished in rolls with polyethylene wrapping to protect against the elements prior to installation, and may be ordered in Master-Paks of fifteen rolls to minimize material handling requirements. Curlex NetFree shall be manufactured in the U.S.A.

Curlex NetFree has a design soil loss ratio (event-based RUSLE C factor) of .063 and is typically suitable for slopes up to 3H:1V. Curlex NetFree is rated for channel flows up to 3.0 ft/s (0.9 m/s) and  $1.0 \text{ lb/ft}^2$  (48 Pa) shear stress<sup>a</sup>.

<sup>a</sup> Curlex NetFree should always be installed in the same direction as anticipated flows.

## **Physical Properties:**

Fiber:	Great Lakes Aspen (naturally seed free)
	Curled, interlocking fibers with barbed edges
Fiber Size:	80% of fibers a minimum of 6 in (15.2 cm) long
	$0.038 \text{ in } \pm 0.008 \text{ in wide } x \ 0.018 \text{ in } \pm 0.003 \text{ in thick}$
	$(0.97 \text{ mm} \pm 0.20 \text{ mm} \text{ wide x } 0.46 \text{ mm} \pm 0.08 \text{ mm} \text{ thick})$
Weight <sup>b</sup> :	$0.73 \text{ lb/yd}^2 (0.40 \text{ kg/m}^2) - 0\% + 15\% @ 22\% \text{ Moisture}$
Thread Material:	Biodegradable
Thread Pattern:	No more than 2.0 in (5.1 cm) transverse stitch spacing

<sup>b</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.



Proud Participant in NTPEP and Proud Member of:

Product Participant of:





# <u>MANUFACTURER'S CERTIFICATION</u> CURLEX<sup>®</sup> NetFree<sup>™</sup> - Erosion Control Blanket

### Manufacturer:

American Excelsior Company 831 Pioneer Avenue Rice Lake, WI 54868 1-866-9FIBERS (1-866-934-2377)

### Project Information (if applicable):

Name:

Location:

Number:

## Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber:	Great Lakes Aspen (naturally seed free)
	Curled, interlocking fibers with barbed edges
Fiber Size:	80% of fibers a minimum of 6 in (15.2 cm) long
	$0.038 \text{ in } \pm 0.008 \text{ in wide x } 0.018 \text{ in } \pm 0.003 \text{ in thick}$
	$(0.97 \text{ mm} \pm 0.20 \text{ mm} \text{ wide x } 0.46 \text{ mm} \pm 0.08 \text{ mm} \text{ thick})$
Blanket Length:	-0 ft (m) + 2.0 ft (0.6 m)
Blanket Width:	-0 in (mm) + 1.0 in (25.4 mm)
Weight <sup>b</sup> :	$0.73 \text{ lb/yd}^2 (0.40 \text{ kg/m}^2) - 0\% + 15\% @ 22\% \text{ Moisture}$
Thread Material:	Biodegradable
Thread Pattern:	No more than 2.0 in (5.1 cm) transverse stitch spacing

<sup>b</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.



Effective Date

**Note:** This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from <u>www.Curlex.com</u> at all times.



850 Avenue H East | Arlington, Texas 76011 Phone 1-800-777-SOIL | Fax 817-385-3585 | <u>www.Curlex.com</u>