

MATERIAL SPECIFICATIONS
CURLEX® EVAPORATIVE COOLING PADS –
GLUED BULK AND FLORAL AIR

Materials:

Great Lakes Aspen
Polypropylene Netting
Adhesive

Sizes:

Min. Width (in / cm)	Max. Width (in / cm)	Min. Length (in / cm)	Max. Length (in / cm)	Weight Per (msi – lb / m ² – kg)
14.0 / 35.6	38.0 / 96.5	16.0 / 40.6	60.0 / 152.4	2.0 / 1.4

Description:

Bulk and Floral Air Cooler Pads are manufactured from Great Lakes Aspen, which are the cleanest, toughest, and most consistent fibers available for evaporative cooling. Bulk Cooler Pads come in a wide variety of sizes to fit all coolers for greenhouse, poultry, and home cooling applications. Bulk Cooler Pads are packaged in compressed bundles and master bundles. Product shall be Manufactured in the U.S.A.

Physical Properties:

Fiber:	Great Lakes Aspen
Fiber Size:	Curled, interlocking fibers with barbed edges 80% of fibers a minimum of 6.0" (15.2 cm) long 0.018" ± 0.003" wide x 0.038" ± 0.008 thick" (0.46 mm ± 0.08 mm wide x 0.97 mm ± 0.20 mm thick)
Pad Width:	- 0" (cm), + 0.5" (1.3 cm)
Pad Length:	- 0" (cm), + 1.0" (2.5 cm)
Weight*:	± 10% @ 22% Moisture
Water Absorption:	250% ± 25%
Netting:	Polypropylene, white
Netting Opening Size:	5/32" wide x 5/32" long (4 mm wide by 4 mm long)
Netting Configuration:	Totally encased
Adhesive:	Wax based adhesive

* Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.



831 Pioneer Avenue | P.O. Box 391 | Rice Lake, Wisconsin 54868
Toll Free 1-866-9FIBERS (1-866-934-2377) or 715-234-6861 | Fax 715-234-6823
www.AmericanExcelsior.com

W0116R0417

MANUFACTURER'S CERTIFICATION
CURLEX® EVAPORATIVE COOLING PADS –
GLUED BULK AND FLORAL AIR

Manufacturer:

American Excelsior Company
831 Pioneer Avenue
Rice Lake, WI 54868
Toll Free 1-866-9FIBERS (1-866-934-2377)

Project Information (if applicable):

Name:

Location:

Number:

Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber:	Great Lakes Aspen
Fiber Size:	Curled, interlocking fibers with barbed edges 80% of fibers a minimum of 6.0" (15.2 cm) long 0.018" ± 0.003" wide x 0.038" ± 0.008 thick" (0.46 mm ± 0.08 mm wide x 0.97 mm ± 0.20 mm thick)
Pad Width:	- 0" (cm), + 0.5" (1.3 cm)
Pad Length:	- 0" (cm), + 1.0" (2.5 cm)
Weight*:	± 10% @ 22% Moisture
Water Absorption:	250% ± 25%
Netting:	Polypropylene, white
Netting Opening Size:	5/32" wide x 5/32" long (4 mm wide by 4 mm long)
Netting Configuration:	Totally encased
Adhesive:	Wax based adhesive

* Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.

TJ 4.4

Tony Johnson – General Manager, Rice Lake

Effective Date

Note: This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from www.AmericanExcelsior.com at all times.



831 Pioneer Avenue | P.O. Box 391 | Rice Lake, Wisconsin 54868
Toll Free 1-866-9FIBERS (1-866-934-2377) or 715-234-6861 | Fax 715-234-6823
www.AmericanExcelsior.com

W0116R0417