









MATERIAL SPECIFICATIONS CURLEX[®] I FIBRENET[™]

Materials:

Great Lakes Aspen (naturally seed free)
Biodegradable Jute Netting
Stitching Thread (UV degradable or biodegradable)
QuickGRASS® (green excelsior – optional)

Typical Roll Sizes:

Width:	4.0 ft (1.2 m)	8.0 ft (2.4 m)
Length:	101.25 ft (30.9 m)	101.25 ft (30.9 m)
Area:	$45.0 \text{ yd}^2 (37.6 \text{ m}^2)$	$90.0 \text{ yd}^2 (75.3 \text{ m}^2)$
Weight:	32.9 lb (14.9 kg)	65.7 lb (29.8 kg)

Description:

Curlex I FibreNet erosion control blanket (ECB) is a natural, stitched excelsior blanket with 100% biodegradable jute netting that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. Product is 100 % biodegradable when biodegradable thread is ordered. Curlex I FibreNet is furnished in rolls with polyethylene wrapping to protect against the elements prior to installation, and may be ordered in Master-Paks of fifteen rolls banded together to minimize material handling requirements. Curlex I FibreNet is also available as QuickGRASS (green pigment). Curlex I FibreNet shall be manufactured in the U.S.A.

Curlex I FibreNet has a design soil loss ratio (event-based RUSLE C factor) of .018 and is typically suitable for slopes up to 2H:1V. Curlex I FibreNet is rated for channel flows up to 7.0 ft/s (2.1 m/s) and 1.75 lb/ft² (84 Pa) shear stress.

Physical Properties:

Fiber: Great Lakes Aspen (naturally seed free)

Curled, interlocking fibers with barbed edges

Fiber Size: 80% of fibers a minimum of 6 in (15.2 cm) long

 $0.038 \text{ in} \pm 0.008 \text{ in wide } \times 0.018 \text{ in} \pm 0.003 \text{ in thick}$

 $(0.97 \text{ mm} \pm 0.20 \text{ mm} \text{ wide x } 0.46 \text{ mm} \pm 0.08 \text{ mm thick})$

Weight^a: $0.73 \text{ lb/yd}^2 (0.40 \text{ kg/m}^2) \pm 10\% @ 22\% \text{ Moisture}$

Thread Pattern: No more than 4.0 in (10.2 cm) transverse stitch spacing

Net Material: Biodegradable Jute

Net Openings: ≈ 0.5 in wide x 1.0 in long (12.7 mm x 25.4 mm)

Net Configuration: Top side only

^a Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.













MANUFACTURER'S CERTIFICATION CURLEX® I FIBRENET™ - Erosion Control Blanket

Manufacturer:

American Excelsior Company 831 Pioneer Avenue Rice Lake, WI 54868 1-866-9FIBERS (1-866-934-2377)

Project Information (if applicable):

Name:

Location:

Number:

Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber: Great Lakes Aspen (naturally seed free)

Curled, interlocking fibers with barbed edges

Fiber Size: 80% of fibers a minimum of 6 in (15.2 cm) long

 $0.038 \text{ in } \pm 0.008 \text{ in wide x } 0.018 \text{ in } \pm 0.003 \text{ in thick}$

 $(0.97 \text{ mm} \pm 0.20 \text{ mm wide x } 0.46 \text{ mm} \pm 0.08 \text{ mm thick})$

Blanket Length: -0 ft (m) + 2.0 ft (0.6 m)

Blanket Width: -0 in (mm) + 1.0 in (25.4 mm)

Weight^a: $0.73 \text{ lb/yd}^2 (0.40 \text{ kg/m}^2) \pm 10\%$ @ 22% Moisture Thread Pattern: No more than 4.0 in (10.2 cm) transverse stitch spacing

Net Material: Biodegradable Jute

Net Openings: ≈ 0.5 in wide x 1.0 in long (12.7 mm x 25.4 mm)

Net Configuration: Top side only

Tony Johnson – General Manager, Rice Lake

Effective Date

Note: This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from www.Curlex.com at all times.



^a Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.