







## MATERIAL SPECIFICATIONS AEC PREMIER STRAW® DOUBLE NET

#### **Materials:**

Certified Weed Seed Free Agricultural Straw Polypropylene Netting Stitching Thread

#### **Roll Sizes:**

Width:	8.0 ft (2.4 m)	16.0 ft (4.9 m)
Length:	112.5 ft (34.3 m)	112.5 ft (34.3 m)
Area:	$100.0 \text{ yd}^2 (83.6 \text{ m}^2)$	$200.0 \text{ yd}^2 (167.2 \text{ m}^2)$
Weight:	50.0 lb (22.7 kg)	100.0 lb (45.4 kg)

#### **Description:**

AEC Premier Straw Double Net erosion control blanket (ECB) is a natural, stitched straw blanket that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. AEC Premier Straw Double Net rolls are stretch wrapped to protect against the elements prior to installation, and may be ordered in Master-Paks of fifteen rolls banded together to minimize handling requirements. AEC Premier Straw Double Net shall be manufactured in the U.S.A.

AEC Premier Straw Double Net has a design soil loss ratio (event-based RUSLE C factor) of .05 and is typically suitable for slopes up to 2H:1V. AEC Premier Straw Double Net is rated for channel flows up to 7.0 ft/s (2.1 m/s) and 1.75 lb/ft² (84 Pa) shear stress.

#### **Physical Properties:**

Fiber: Certified Weed Seed Free Agricultural Straw Fiber Size: 75% of fibers a minimum of 4 in (10.2 cm) long

Weight<sup>a</sup>:  $0.50 \text{ lb/yd}^2 (0.27 \text{ kg/m}^2) \pm 10\%$ 

Thread Pattern: No more than 2.0 in (5.1 cm) transverse stitch spacing

Net Material: Polypropylene (green with oxo-biodegrader and UV degrader

additives or white with UV degrader additive)

Net Openings: 0.5 in wide by 0.5 in long (12.7 mm x 12.7 mm)

Net Configuration: Top and bottom

<sup>&</sup>lt;sup>a</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of AEC Premier Straw fibers is 15%.











# MANUFACTURER'S CERTIFICATION AEC PREMIER STRAW® DOUBLE NET - Erosion Control Blanket

#### **Manufacturer:**

American Excelsior Company 831 Pioneer Avenue Rice Lake, WI 54868 1-866-9FIBERS (1-866-934-2377)

<b>Project</b>	Inform	ation	(if annl	icahle).
LIVICLE	11111/11 111	auwn	ui addi	icame,

Name:		
<b>Location:</b>		
Number:		

### Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber: Certified Weed Seed Free Agricultural Straw Fiber Size: 75% of fibers a minimum of 4 in (10.2 cm) long

Blanket Length: -0 ft (m), +5% (upon application) Blanket Width: -0 in (mm) + 1.0 in (25.4 mm) Weight<sup>a</sup>:  $0.50 \text{ lb/yd}^2 (0.27 \text{ kg/m}^2) \pm 10\%$ 

Thread Pattern: No more than 2.0 in (5.1 cm) transverse stitch spacing

Net Material: Polypropylene (green with oxo-biodegrader and UV degrader

additives or white with UV degrader additive)

Net Openings: 0.5 in wide by 0.5 in long (12.7 mm x 12.7 mm)

Net Configuration: Top and bottom

Rocky Van Gilder – V.P. of Wood Operations Effective Date

**Note:** This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from <a href="https://www.Curlex.com">www.Curlex.com</a> at all times.



<sup>&</sup>lt;sup>a</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of AEC Premier Straw fibers is 15%.