







# **Product Information and Application Guidelines**

### **Degradable Erosion Control Blankets (ECBs)**





	Channels					125		
	Product	Permissible Shear Stress [lb/ft² (Pa)]	Permissible Velocity [ft/s (m/s)]	Slope	Functional Longevity (months) <sup>a</sup>	Matrix	QuickGRASS® Option	FibreNet <sup>™</sup> Option
	Curlex <sup>®</sup> NetFree <sup>™</sup>	1.0 (48)	3.0 (0.9)	≤3H:1V	≤ 18 (100% biodegradable)	Great Lakes Aspen (naturally seed free)		
	AEC Premier Straw <sup>®</sup> Single Net	1.55 (74)	4.5 (1.4)	≤3H:1V	≤ 12	Agricultural Straw (certified weed seed free)		<b>√</b>
	Curlex <sup>®</sup> I CL	1.60 (77)	5.0 (1.5)	≤2H:1V	≤ 15	Great Lakes Aspen (naturally seed free)		
	AEC Premier Straw <sup>®</sup> Double Net	1.75 (84)	7.0 (2.1)	≤2H:1V	≤ 12	Agricultural Straw (certified weed seed free)		V
	Curlex <sup>®</sup> I	1.75 (84)	7.0 (2.1)	≤2H:1V	≤ 18	Great Lakes Aspen (naturally seed free)	<b>√</b>	<b>√</b>
	Curlex <sup>®</sup> II CL	1.80 (86)	7.3 (2.2)	≤1.5H:1V	≤ 18	Great Lakes Aspen (naturally seed free)		
	AEC Premier Straw/Coconut <sup>TM</sup>	2.0 (96)	8.5 (2.6)	≤1.5H:1V	≤ 24	70% Straw (certified weed seed free) & 30% Coconut		<b>√</b>
	Curlex <sup>®</sup> II	2.25 (108)	9.0 (2.7)	≤1.5H:1V	≤ 24	Great Lakes Aspen (naturally seed free)	7	~
+++++	AEC Premier Coconut <sup>™</sup>	2.25 (108)	9.0 (2.7)	≤1H:1V	≤ 36	Coconut		<b>√</b>
	Curlex <sup>®</sup> II .98	2.5 (120)	10.0 (3.1)	≤1H:1V	≤ 30	Great Lakes Aspen (naturally seed free)	<b>V</b>	<b>√</b>
	Curlex <sup>®</sup> III	2.5 (120)	10.0 (3.1)	≤1H:1V	≤ 36	Great Lakes Aspen (naturally seed free)	<b>√</b>	<b>√</b>
	Curlex <sup>®</sup> High Velocity <sup>™</sup>	3.25 (156)	11.0 (3.4)	≤.75H:1V	36 +	Great Lakes Aspen (naturally seed free)	<b>√</b>	√

	Channels		Turf Reinforcement Mats (TRMs)			
Product	Permissible Shear Stress [lb/ft² (Pa)]	Permissible Velocity [ft/s (m/s)]	Slope	Functional Longevity (months) <sup>a</sup>	Matrix	Color Option
Recyclex® TRM - V	8+ (384+)	16+ (4.9+)	≤ 0.5H:1V	Permanent	Crimped Recycled Polyester	Green or Brown <sup>c</sup>
Curlex <sup>®</sup> Enforcer <sup>® b</sup>	10 (480)	17 (5.2)	≤ 0.5H:1V	Permanent	Great Lakes Aspen (naturally seed free)	QuickGRASS® or Natural
Recyclex <sup>®</sup> TRM	10+ (480+)	17+ (5.2+)	≤ 0.5H:1V	Permanent	Crimped Recycled Polyester	Green or Brown <sup>c</sup>

#### Sediment Control/Shoreline and Streambank Stabilization



Seament Control/Shorenic and Streambank Stabilization					
Product	Functional Longevity (months) <sup>a</sup>	Matrix	Applications	Sediment Control	Shoreline & Streambank Stabilization
Curlex <sup>®</sup> SiltTRAP <sup>™</sup>	≤ 24	Great Lakes Aspen (naturally seed free)	≤8H:1V slope, Non channelized flow conditions	V	
Curlex® Sediment Log®	≤ 24	Great Lakes Aspen (naturally seed free)	In channels, across slopes, inlet protection, perimeter control	V	
AEC Premier Straw <sup>®</sup> Wattle	≤ 18	Agricultural Straw (certified weed seed free)	Low flow channel bottoms, across slopes	<b>√</b>	
Curlex <sup>®</sup> Bloc	≥ 36	Great Lakes Aspen (naturally seed free)	Shoreline and Streambank Stabilization and other applications	√	V

## **Hydraulic Mulch**



Product	Materials	Functional Longevity (months) <sup>a</sup>	Slope Application
Bindex <sup>™</sup> BFM	Natural Wood Fibers (including Curlex Fibers), High Grade Organic Tackifier, Cross-linked Binder, and Green Dye	≤9	≤1H:1V
Bindex <sup>™</sup> Wood WT	Natural Wood Fibers (including Curlex Fibers), High Grade Organic Tackifier, and Green Dye	≤4	≤3H:1V
Bindex <sup>™</sup> Blend WT	Natural Wood Fibers (including Curlex Fibers), Recycled Clean Paper, High Grade Organic Tackifier, and Green Dye	≤3	≤ 3.5H:1V
Bindex <sup>™</sup> Wood	Natural Wood Fibers (including Curlex Fibers and Green Dye	≤ 4	≤ 5H:1V
Bindex <sup>™</sup> Blend	Natural Wood Fibers (including Curlex Fibers), Recycled Clean Paper, and Green Dye	≤ 3	≤ 5H:1V
Excel® Fibermulch II  Great Lakes Aspen (naturally seed free), Dri- Water Hydro Mix Tackifier, and Green Dye		≤ 3	≤4H:1V

#### Accessories



Product	Materials	Application	
E-Staple <sup>®</sup> (4 in or 6 in)	100% Biodegradable Resins	Staples for anchoring rolled erosion control products and turf	
U-Shaped Steel Wire Staples (11gauge, 6.0 in x 1.0 in x 6.0 in) (8 gauge, 8.0 in x 2.0 in x 8.0 in)	Hard Drawn Steel Wire	Staples for anchoring rolled erosion control products and turf	

<sup>&</sup>lt;sup>a</sup> Functional longevity varies by region due to differences in climatic conditions. <sup>b</sup> Curlex Enforcer is a biocomposite turf reinforcement mat. <sup>c</sup> Special order item