



**TriNet® Curlex®
EROSION CONTROL BLANKET
SPECIFICATION**

PART I - GENERAL

1.01 Summary

- A. The biocomposite Turf Reinforcement Mat (TRM) contains excelsior wood fiber for the purpose of erosion control and revegetation as described herein.
- B. This work shall consist of furnishing and installing the biocomposite TRM; including fine grading, blanketing, stapling, and miscellaneous related work, in accordance with these standard specifications and at the locations identified on drawings or designated by the owner's representative. This work shall include all necessary materials, labor, supervision, and equipment for installation of a complete system.
- C. All work of this section shall be performed in accordance with the conditions and requirements of the contract documents.
- D. The biocomposite TRM shall be used to prevent surface erosion and enhance revegetation. Based on a project-by-project engineering analysis, the biocomposite TRM shall be suitable for the following applications:
 - 1. Slope protection
 - 2. Channel and ditch linings
 - 3. Reservoir embankments and spillways
 - 4. Culvert inlets and outfalls
 - 5. Dikes, levees, and riverbanks

1.02 Performance Requirements

- A. Biocomposite TRM shall provide a cover material to enhance germination, reduce slope and/or channel erosion, and permanently reinforce vegetation.
- B. Biocomposite TRM performance requirements:

Slopes ^a :	≤ .5H:1V (ASTM D6459)
C factor ^a :	.031 (ASTM D6459)
Shear Stress ^a :	13.0 lbs/ft ² (622 Pa) (ASTM D6460)
Velocity ^a :	20.0 ft/sec (6.1 m/sec) (ASTM D6460)
Functional Longevity ^b :	≤ 36 months (fibers only) / Permanent

^a Slope and channel performance ratings are based on typical industry values.

^b Functional Longevity varies from region to region because of differences in climatic conditions.



1.03 Submittals

- A. Submittals shall include complete design data, Product Data Sheets, Product Netting Information, SDS, Staple Pattern Guides, Installation Guidelines, Manufacturing Material Specifications, Manufacturing Certifications, CAD details, and a Manufacturing Quality Control Program. In addition, the Manufacturer shall provide a test report providing data showing the performance capabilities of the biocomposite TRM along with reference installations similar in size and scope to that specified for the project.

1.04 Delivery, Storage, and Handling

- A. Biocomposite TRM shall be furnished in rolls and wrapped with suitable material to protect against moisture intrusion and extended ultraviolet exposure prior to placement. Each roll shall be labeled with a date code identification, which allows for sufficient tracking of the product back to date of manufacturing and for quality control purposes.
- B. Biocomposite TRM shall be of consistent thickness with fibers distributed evenly over the entire area of the blanket.
- C. Biocomposite TRM shall be free of defects and voids that would interfere with proper installation or impair performance.
- D. Biocomposite TRM shall be stored by the Contractor in a manner that protects them from damage by construction activities.

PART II - PRODUCTS

2.01 Biocomposite TRM

- A. Biocomposite TRM shall be TriNet Curlex, as manufactured by American Excelsior Company, Arlington, TX (1-866-9FIBERS).
- B. TriNet Curlex a three dimensional biocomposite Turf Reinforcement Mat (TRM) consists of a specific cut of naturally seed free Great Lakes Aspen curled wood excelsior with 80% of the fiber \geq 6 inches in length. It is of consistent thickness with fibers evenly distributed throughout the entire area of the blanket. The top and middle of each blanket has the ultra-heavy duty UV stabilized polypropylene netting with a heavy duty polypropylene UV stabilized bottom net. TriNet Curlex shall be manufactured in the U.S.A.



C. Biocomposite TRM shall have the following material characteristics:

Width		8.0 ft (2.4 m)	16.0 ft (4.9 m)
Length		67.5 ft (20.6 m)	67.5 ft (20.6 m)
Area		60.0 yd ² (50.2 m ²)	120.0 yd ² (100.34 m ²)
Weight^c		74.34 lb (33.72 kg)	148.68 lb (67.44 kg)
Fiber Count		≈ 7,000 per yd ² (≈ 8,400 per m ²)	≈ 7,000 per yd ² (≈ 8,400 per m ²)
Fiber Length (80% min.)		≈ 6.0 in (≈ 15.2 cm)	≈ 6.0 in (≈ 15.2 cm)
Curlex Fiber Matrix (± 10%)		0.730 lb/yd ² (0.396 kg/m ²)	0.73 lb/yd ² (0.396 kg/m ²)
Product Weight (± 10%)		1.239 lb/yd ² (0.672 kg/m ²)	1.239 lb/yd ² (0.672 kg/m ²)
Net Openings	Top - Ultra Heavy Duty Polypropylene (UV-Stabilized)	0.45 in x 0.58 in (11.43 mm x 14.73 mm)	0.45 in x 0.58 in (11.43 mm x 14.73 mm)
	Middle - Ultra Heavy Duty Polypropylene (UV-Stabilized)	0.45 in x 0.58 in (11.43 mm x 14.73 mm)	0.45 in x 0.58 in (11.43 mm x 14.73 mm)
	Bottom - Super Heavy Duty Polypropylene (UV-Stabilized)	0.5 in x 0.5 in (12.7 mm x 12.7 mm)	0.5 in x 0.5 in (12.7 mm x 12.7 mm)

TYPICAL INDEX VALUES

<u>Index Property</u>	<u>Test Method</u>	<u>Value</u>
Thickness	ASTM D 6525	0.304 in (7.72 mm)
Light Penetration	ASTM D 6567	21.5%
Resiliency	ASTM D 1777/ECTC	74%
Mass per Unit Area	ASTM D 6475	0.976 lb/yd ² (0.529 kg/m ²)
MD-Tensile Strength Max.	ASTM D 6818	800 lb/ft (11.68 kN/m)
TD-Tensile Strength Max.	ASTM D 6818	800 lb/ft (11.68 kN/m)
MD-Elongation	ASTM D 6818	17%
TD-Elongation	ASTM D 6818	17%
Swell	ECTC Procedure	80%
Water Absorption	ASTM D 1117/ECTC	150%
UV Stability	ASTM D 4355 (1,000 hr)	90% minimum
Porosity	ECTC Procedure	94.89%
Stiffness	ASTM D6575	2.47 oz-in
Bench-Scale Rain Splash	ASTM D 7101	SLR = 22.10 @ 2 in/hr ^{d,e}
Bench-Scale Rain Splash	ASTM D 7101	SLR = 11.75 @ 4 in/hr ^{d,e}
Bench-Scale Rain Splash	ASTM D 7101	SLR = 11.12 @ 6 in/hr ^{d,e}
Bench-Scale Shear	ASTM D 7207	4.2 lb/ft ² @ 0.5 in soil loss ^e
Germination Improvement	ASTM D 7322	372%

^c Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.

^d SLR is the Soil Loss Ratio, as reported by NTPEP/AASHTO. ^e Bench-scale index values should not be used for design purposes.

2.02 Staples

- A. Staples shall be U-shaped, 11 gauge steel wire and shall be 1 inch wide by 6 inches long, or 2 inches wide by 8 inches long.

PART III - EXECUTION

3.01 Blanket Supplier Representation

- A. Contractor shall coordinate with the biocomposite TRM supplier for a qualified representative to be present at the job site on the start of installation to provide technical assistance as needed. Contractor shall remain solely responsible for the quality of installation.



3.02 Site Preparation

- A. Before placing biocomposite TRM, the Contractor shall certify that the subgrade has been properly compacted, has been graded smooth, has no depressions, voids, soft or uncompacted areas, is free from obstructions such as tree roots, protruding stones or other foreign matter, and is seeded and fertilized according to project specifications. The Contractor shall not proceed until all unsatisfactory conditions have been remedied. By beginning construction, the Contractor signifies that the preceding work is in conformance with this specification.
- B. Contractor shall fine grade the subgrade by hand dressing where necessary to remove local deviations.
- C. No vehicular traffic shall be permitted directly on the biocomposite TRM.

NOTE: Topsoiling, seeding, and fertilizing is not included in this specification.

3.03 Slope Installation

- A. Biocomposite TRM shall be installed as directed by the owner's representative in accordance with manufacturer's Installation Guidelines, Staple Pattern Guides, and CAD details. The extent of biocomposite TRM shall be as shown on the project drawings.
- B. Biocomposite TRM shall be orientated in vertical strips and anchored with staples, as identified in the Staple Pattern Guide. Adjacent strips shall be abutted or overlapped to allow for installation of a common row of staples that anchor through the nettings of both biocomposite TRMs. Horizontal joints between biocomposite TRM shall be sufficiently overlapped with the uphill end on top for a common row of staples so that the staples anchor through the nettings of both biocomposite TRMs.
- C. Where exposed to overland sheet flow, a trench shall be located at the uphill termination. Biocomposite TRM shall be stapled to the bottom of the trench. The trench shall be backfilled and compacted. Where feasible, the uphill end of the biocomposite TRM shall be extended three feet over the crest of the slope.
- D. Slope biocomposite TRM shall be overlapped by the channel biocomposite TRM sufficiently for a common row of staples to anchor through the nettings of both biocomposite TRMs when terminating into a channel.

3.04 Channel Installation

- A. Biocomposite TRM shall be installed as directed by the owner's representative in accordance with manufacturer's Installation Guidelines, Staple Pattern Guides, and CAD details. The extent of biocomposite TRM shall be as shown on the project drawings.
- B. Biocomposite TRM shall be installed parallel to the flow of water. The first roll shall be centered longitudinally in mid-channel and anchored with staples as identified in the Staple Pattern Guide. Subsequent rolls shall follow from channel center outward and be overlapped to allow installation of a common row of staples so that the staples anchor through the nettings of both biocomposite TRMs.
- C. Successive lengths of biocomposite TRM shall be overlapped sufficiently for a common row of staples with the upstream end on top. Staple the overlap across the end of each of the overlapping lengths so that staples anchor through the nettings of both biocomposite TRMs.



- D. A termination trench shall be located at the upstream termination. Biocomposite TRM shall be stapled to the bottom of the trench. The trench shall be backfilled and compacted.

3.05 Quality Assurance

- A. Biocomposite TRM shall not be defective or damaged. Damaged or defective materials shall be replaced at no additional cost to the owner.
- B. Product shall be manufactured in accordance to a documented Quality Control Program. At a minimum, the following procedures and documentation shall be provided upon request:
 1. Manufacturing Quality Control Program Manual
 2. First piece inspection and documentation of products produced to assure component materials and finished product tolerances are within manufacturer specifications.
 3. Additional inspections for product conformance shall be conducted during the run after the first piece inspection.
 4. Moisture content readings recorded for each manufacturing day.
 5. Recorded weight of every erosion control blanket manufactured.
 6. Each individual erosion control blanket shall be inspected, weighed, and documented prior to packaging for conformance to manufacturing specifications.
 7. Documentation and record retention for at least two years.

3.06 Clean-up

- A. At the completion of this scope of work, Contractor shall remove from the job site and properly dispose of all remaining debris, waste materials, excess materials, and equipment required of or created by Contractor. Disposal of waste materials shall be solely the responsibility of Contractor and shall be done in accordance with applicable waste disposal regulations.

3.07 Method of Measurement

- A. The biocomposite TRM shall be measured by the square yard of surface area covered. No measurement for payment shall be made for overlaps, fine grading, trenching, staples, or other miscellaneous materials necessary for placement of the erosion control biocomposite TRM.

3.08 Basis of Payment

- A. The accepted quantities of biocomposite TRM shall be paid for at the contract unit price per square yard, complete in place.

Payment shall be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
Biocomposite TRM	Square Yards

Disclaimer: TriNet Curlex is a system for erosion control and revegetation on slopes and channels. American Excelsior Company (AEC) believes that the information contained herein to be reliable and accurate for use in erosion control and re-vegetation applications. However, since physical conditions vary from job site to job site and even within a given job site, AEC makes no performance guarantees and assumes no obligation or liability for the reliability or accuracy of information contained herein for the results, safety, or suitability of using TriNet Curlex, or for damages occurring in connection with the installation of any erosion control product whether or not made by AEC or its affiliates, except as separately and specifically made in writing. These specifications are subject to change without notice.



850 Avenue H East | Arlington, Texas 76011
 Phone 1-800-777-SOIL | Fax 817-385-3585 | www.Curlex.com