



INDEX™ WOOD and INDEX™ BLEND HYDRAULIC MULCH INSTALLATION GUIDELINES

Before hydraulically applying Bindex Wood or Bindex Blend products, the site shall be inspected by the Owner's Representative to ensure the area to be protected is geotechnically stable. In addition, areas to be protected should be designed to prevent run-on conditions. Bindex Wood and Bindex Blend products shall not be used in channels or areas of concentrated flow. The contractor shall proceed when all satisfactory conditions are present.

Each bag [\approx 50lb (22.7 kg)] of Bindex Wood or Bindex Blend products should be mixed with approximately 100 gallons (378.5 L) of water and applied at a rate of 2,000 – 3,000 lb/acre (2,242 – 3,363 kg/ha). Mixing and application rates shall always be matched to project-specific specifications.

Apply Bindex Wood or Bindex Blend products from two directions for best coverage results.

Disclaimer: Bindex Wood and Bindex Blend products are systems for erosion control and revegetation on slopes. American Excelsior Company (AEC) believes that the information contained herein to be reliable and accurate for use in erosion control and revegetation applications. However, since physical conditions vary from job site to job site and even within a given job site, AEC makes no performance guarantees and assumes no obligation or liability for the reliability or accuracy of information contained herein, for the results, safety, or suitability of using Bindex Wood or Bindex Blend products, or for damages occurring in connection with the installation of any erosion control product whether or not made by AEC or its affiliates, except as separately and specifically made in writing by AEC. These guidelines are subject to change without notice.