



MATERIAL SPECIFICATIONS CURLEX® I CL

Materials:

Great Lakes Aspen (naturally seed free)
Polypropylene Netting
Stitching Thread
QuickGRASS® (green excelsior – optional)

Typical Roll Sizes:

| | | | |
|---------|---------------------------------------------|-----------------------------------------------|-----------------------------------------------|
| Width: | 4.0 ft (1.2 m) | 8.0 ft (2.4 m) | 16.0 ft (4.9 m) |
| Length: | 150.0 ft (45.7 m) | 150.0 ft (45.7 m) | 150.0 ft (45.7 m) |
| Area: | 66.7 yd ² (55.7 m ²) | 133.3 yd ² (111.5 m ²) | 266.7 yd ² (223.0 m ²) |
| Weight: | 36.7 lb (16.6 kg) | 73.3 lb (33.3 kg) | 146.7 lb (66.5 kg) |

Description:

Curlex I CL erosion control blanket (ECB) is a natural, stitched excelsior blanket that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. Curlex I CL is furnished in rolls with polyethylene wrapping to protect against the elements prior to installation, and may be ordered in Master-Paks of fifteen rolls banded together to minimize material handling requirements. Curlex I CL is also available as QuickGRASS (green pigment). Curlex I CL shall be manufactured in the U.S.A.

Curlex I CL has a design soil loss ratio (event-based RUSLE C factor) of .039 and is typically suitable for slopes up to 2H:1V. Curlex I CL is rated for channel flows up to 5.0 ft/s (1.5 m/s) and 1.60 lb/ft² (77 Pa) shear stress.

Physical Properties:

| | |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fiber: | Great Lakes Aspen (naturally seed free) Curled, interlocking fibers with barbed edges |
| Fiber Size: | 80% of fibers a minimum of 6 in (15.2 cm) long 0.038 in ± 0.008 in wide x 0.018 in ± 0.003 in thick (0.97 mm ± 0.20 mm wide x 0.46 mm ± 0.08 mm thick) |
| Weight ^a : | 0.55 lb/yd ² (0.30 kg/m ²) ± 10% @ 22% Moisture |
| Thread Pattern: | No more than 4.0 in (10.2 cm) transverse stitch spacing |
| Net Material: | Polypropylene (green with oxo-biodegrader and UV degrader additives or white with UV degrader additive) |
| Net Openings: | 1.0 in wide x 2.0 in long (25.4 mm wide x 50.8 mm long) |
| Net Configuration: | Top side only |

^a Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.





MANUFACTURER'S CERTIFICATION
CURLEX® I CL - Erosion Control Blanket

Manufacturer:

American Excelsior Company
831 Pioneer Avenue
Rice Lake, WI 54868
1-866-9FIBERS (1-866-934-2377)

Project Information (if applicable):

Name:

Location:

Number:

Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

| | |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fiber: | Great Lakes Aspen (naturally seed free) Curled, interlocking fibers with barbed edges |
| Fiber Size: | 80% of fibers a minimum of 6 in (15.2 cm) long 0.038 in \pm 0.008 in wide x 0.018 in \pm 0.003 in thick (0.97 mm \pm 0.20 mm wide x 0.46 mm \pm 0.08 mm thick) |
| Blanket Length: | -0 ft (m) + 2.0 ft (0.6 m) |
| Blanket Width: | -0 in (mm) + 1.0 in (25.4 mm) |
| Weight ^a : | 0.55 lb/yd ² (0.30 kg/m ²) \pm 10% @ 22% Moisture |
| Thread Pattern: | No more than 4.0 in (10.2 cm) transverse stitch spacing |
| Net Material: | Polypropylene (green with oxo-biodegrader and UV degrader additives or white with UV degrader additive) |
| Net Openings: | 1.0 in wide x 2.0 in long (25.4 mm wide x 50.8 mm long) |
| Net Configuration: | Top side only |

^a Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.

TJ 4.4

Tony Johnson - General Manager, Rice Lake

Effective Date

Note: This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacturer's Certifications (MSMC) for AEC products shall be accessed from www.Curlex.com at all times.

