



**BINDEX™ WOOD / EXCEL® FIBERMULCH II HYDRAULIC MULCH
INSTALLATION GUIDELINES**

Before hydraulically applying Bindex Wood / Excel Fibermulch II, the finished grade shall be inspected by the Owner's Representative to ensure it has been properly compacted and fine graded to remove any existing rills. It shall be free of obstructions, such as tree roots, projections such as stones, and other foreign objects. The contractor shall proceed when all satisfactory conditions are present. Each bag [\approx 50 lb (22.7 kg)] of Bindex Wood / Excel Fibermulch II should be mixed with approximately 100 gallons (378.5 L) of water and applied at a rate of 2,000 – 2,500 lb/acre (2,241.8 kg/ha – 2,802.2 kg/ha). Mixing and application rates shall always be matched to project-specific specifications. A green tracer dye (optional) shall be mixed with water in tank before being applied. Apply Bindex Wood / Excel Fibermulch II in multiple directions for best coverage results.

Disclaimer: Bindex Wood / Excel Fibermulch II is a system for erosion control and revegetation on slopes. American Excelsior Company (AEC) believes that the information contained herein to be reliable and accurate for use in erosion control and revegetation applications. However, since physical conditions vary from job site to job site and even within a given job site, AEC makes no performance guarantees and assumes no obligation or liability for the reliability or accuracy of information contained herein, for the results, safety, or suitability of using Bindex Wood / Excel Fibermulch II, or for damages occurring in connection with the installation of any erosion control product whether or not made by AEC or its affiliates, except as separately and specifically made in writing by AEC. These guidelines are subject to change without notice.