



MATERIAL SPECIFICATIONS CURLEX® ROADRUNNER™ DOUBLE NET

Materials:

Great Lakes Aspen (naturally seed-free)
Polypropylene Netting
Stitching Thread
QuickGRASS® (green excelsior – optional)

Typical Roll Sizes:

Width:	8.0 ft (2.4 m)
Length:	550.0 ft (167.6 m)
Area:	488.9 yd ² (408.8 m ²)
Weight:	356.9 lb (162.0 kg)

Description:

Curlex RoadRunner Double Net erosion control blanket (ECB) is a mechanically-installed, stitched excelsior blanket that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten revegetation. Curlex RoadRunner Double Net significantly speeds up the unrolling process. Curlex RoadRunner Double Net is furnished in rolls with polyethylene wrapping and a 4 in cardboard core for mechanical installation. Curlex RoadRunner Double Net is also available as QuickGRASS (green pigment). Curlex RoadRunner Double Net shall be manufactured in the U.S.A.

Curlex RoadRunner Double Net has a soil loss ratio (event-based RUSLE C factor) of .022 and is typically suitable for slopes up to 1.5H:1V^a. Curlex RoadRunner Double Net is rated for channel flows up to 9.0 ft/s (2.7 m/s) and 2.25 lb/ft² (108 Pa) shear stress.

^a Slope steepness is dependent on the safe operating limits of the installation equipment. Refer to equipment safety manual.

Physical Properties:

Fiber:	Great Lakes Aspen (naturally seed-free) Curled, interlocking fibers with barbed edges
Weight ^b :	0.73 lb/yd ² (0.40 kg/m ²) ± 10% @ 22% Moisture
Thread Pattern:	No more than 4.0 in (10.2 cm) transverse stitch spacing
Net Material:	Polypropylene (green with oxo-biodegrader and UV degrader additives or white with UV degrader additive)
Net Openings:	1.0 in wide x 2.0 in long (25.4 mm wide x 50.8 mm long)
Net Configuration:	Top and bottom

^b Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.





MANUFACTURER'S CERTIFICATION
CURLEX® ROADRUNNER™ DOUBLE NET - Erosion Control Blanket

Manufacturer:

American Excelsior Company
831 Pioneer Avenue
Rice Lake, WI 54868
1-866-9FIBERS (1-866-934-2377)

Project Information (if applicable):

Name:

Location:

Number:

Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber:	Great Lakes Aspen (naturally seed-free) Curled, interlocking fibers with barbed edges
Blanket Length:	-0 ft (m) + 2.0 ft (0.6 m)
Blanket Width:	-0 in (mm) + 1.0 in (25.4 mm)
Weight ^b :	0.73 lb/yd ² (0.40 kg/m ²) ± 10% @ 22% Moisture
Thread Pattern:	No more than 4.0 in (10.2 cm) transverse stitch spacing
Net Material:	Polypropylene (green with oxo-biodegrader and UV degrader additives or white with UV degrader additive)
Net Openings:	1.0 in wide x 2.0 in long (25.4 mm wide x 50.8 mm long)
Net Configuration:	Top and bottom

^b Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.

Tony Richter – General Manager, Rice Lake

Effective Date

Note: This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from www.Curlex.com at all times.

