



PRODUCT DATA SHEET
CURLEX® SFW
(Biodegradable Version)

DESCRIPTION

Curlex SFW consists of naturally seed-free Great Lakes Aspen wood excelsior inside a 100% biodegradable, durable, flexible tubular netting with knotted ends. Curlex SFW is designed to provide intimate contact with the soil, which prevents blowouts and undermining. Curlex SFW may be placed across channel bottoms, on hillslopes, around inlet structures, or any other applications where straw wattles are used. Curlex SFW shall be manufactured in the U.S.A.

PHYSICAL PROPERTIES

Curlex SFW measurements at time of manufacturing:

PROPERTY	ENGLISH	METRIC
Product Name	9 in	22.9 cm
	12 in	30.5 cm
	20 in	50.8 cm
Minimum Diameter	8.5 in	21.6 cm
	11.5 in	29.2 cm
	19.0 in	48.3 cm
Curlex SFW Density ^b (± 10%)	(9 in) 4.53 lb/ft ³	72.56 kg/m ³
	(12 in) 3.82 lb/ft ³	61.19 kg/m ³
	(20 in) 2.75 lb/ft ³	44.05 kg/m ³
Curlex SFW Dimensions (W x L) (± 10%)	9 in x 25 ft	0.2290 m x 7.620 m
	12 in x 10.0 ft	0.3048 m x 3.048 m
	20 in x 10.0 ft	0.508 m x 3.048 m

