







## PRODUCT DATA SHEET CURLEX® SEDIMENT LOG® (Biodegradable Version)

## DESCRIPTION

Curlex Sediment Log consists of a specific cut of naturally seed free Great Lakes Aspen wood excelsior with 80% of the fiber  $\geq 6$  inches in length inside a biodegradable, durable, flexible tubular containment material. Curlex Sediment Log shall be manufactured in the U.S.A. at company locations where QA/QC is implemented and managed by the manufacturer. Curlex/Curlex fibers are listed with the EPA as an approved/pre-approved sorbent.

## PHYSICAL PROPERTIES

Curlex Sediment Log measurements at time of manufacturing:

annient Zeg metataren				
Product Name/Nominal Diameter	6.0 in	9.0 in	12.0 in	20.0 in
Minimum	5.5 in	8.0 in	11.0 in	18.0 in
Diameter	(14.0 cm)	(20.3 cm)	(27.9 cm)	(45.7  cm)
Length	25.0 ft	25.0 ft	10.0 ft	10.0 ft
$(\pm 10\%)$	(7.6  m)	(7.6  m)	(3.1  m)	(3.1  m)
Weight <sup>a</sup>	12.0 lb	25.0 lb	20.0 lb	30.0 lb
$(\pm 10\%)$	(5.4  kg)	(11.3  kg)	(9.1 kg)	(13.6  kg)
Density <sup>a</sup>	2.44 lb/ft <sup>3</sup>	2.26 lb/ft <sup>3</sup>	2.54 lb/ft <sup>3</sup>	1.38 lb/ft <sup>3</sup>
$(\pm 10\%)$	$(39.09 \text{ kg/m}^3)$	$(36.20 \text{ kg/m}^3)$	$(40.69 \text{ kg/m}^3)$	$(22.11 \text{ kg/m}^3)$

## **CURLEX SEDIMENT LOG PERFORMANCE REQUIREMENTS**

Property	Value	Method	
Flow Rate	$\geq$ 35 GPM/ft <sup>2</sup>	ASTM D5141	
Soil Retention Effectiveness	$\geq$ 96%	ASTM D7351	
Channel Soil Loss Reduction	≥ 50%	ASTM D7208	
pH Buffering	$8 \pm 3$	ASTM D1117, modified	
Functional Longevity <sup>b</sup>	$\leq$ 24 months	Documented laboratory and field studies	
Removal of Polynuclear			
Aromatic Hydrocarbons (PAHs)	≥ 95%	Quantified research <sup>c</sup>	
Fly Ash Filtration (TSS)	≥ 78%	Quantified research <sup>d</sup>	
Fly Ash Filtration (NTU)	≥ 76%	Quantified research <sup>d</sup>	

<sup>&</sup>lt;sup>a</sup> Weight and density are based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.



<sup>&</sup>lt;sup>b</sup> Functional longevity varies from region to region because of differences in climatic conditions.

<sup>&</sup>lt;sup>c</sup> Boving and Zhang, Chemosphere 54 (2004) 831-839.

<sup>&</sup>lt;sup>d</sup> Kelsey, K. and M. Murley. (2017, January). Fly Ash Slurry Filtration Using Curlex<sup>®</sup> Sediment Log<sup>®</sup> - Quantifying Total Suspended Solids and Turbidity Reduction. Unpublished internal document, ErosionLab.