



PRODUCT DATA SHEET
CURLEX® SEDIMENT LOG®

DESCRIPTION

Curlex Sediment Log consists of a specific cut of naturally seed free Great Lakes Aspen wood excelsior inside a degradable, durable, flexible tubular containment material. Curlex Sediment Log shall be manufactured in the U.S.A. at company locations where QA/QC is implemented and managed by the manufacturer. Curlex is made from fibers which are listed by the EPA as a known sorbent.

PHYSICAL PROPERTIES

Curlex Sediment Log measurements at time of manufacturing:

Product Name/Nominal Diameter	6.0 in	9.0 in	12.0 in	20.0 in
Minimum Diameter	5.5 in (14.0 cm)	8.0 in (20.3 cm)	11.0 in (27.9 cm)	18.0 in (45.7 cm)
Length (± 10%)	25.0 ft (7.6 m)	25.0 ft (7.6 m)	10.0 ft (3.1 m)	10.0 ft (3.1 m)
Weight ^a (± 10%)	12.0 lb (5.4 kg)	25.0 lb (11.3 kg)	20.0 lb (9.1 kg)	30.0 lb (13.6 kg)
Density ^a (± 10%)	2.44 lb/ft ³ (39.09 kg/m ³)	2.26 lb/ft ³ (36.20 kg/m ³)	2.54 lb/ft ³ (40.69 kg/m ³)	1.38 lb/ft ³ (22.11 kg/m ³)

CURLEX SEDIMENT LOG PERFORMANCE REQUIREMENTS

Property	Value	Method
Flow Rate	≥ 35 GPM/ft ²	ASTM D5141
Soil Retention Effectiveness	≥ 96%	ASTM D7351
Channel Soil Loss Reduction	≥ 50%	ASTM D7208
pH Buffering	8 ± 3	ASTM D1117, modified
Functional Longevity ^b	≤ 24 months	Documented laboratory and field studies
Removal of Polynuclear Aromatic Hydrocarbons (PAHs)	≥ 95%	Quantified research ^c
Fly Ash Filtration (TSS)	≥ 78%	Quantified research ^d
Fly Ash Filtration (NTU)	≥ 76%	Quantified research ^d

^a Weight and density are based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.

^b Functional longevity varies from region to region because of differences in climatic conditions.

^c Boving and Zhang, Chemosphere 54 (2004) 831-839.

^d Kelsey, K. and M. Murley. (2017, January). Fly Ash Slurry Filtration Using Curlex® Sediment Log® - Quantifying Total Suspended Solids and Turbidity Reduction. Unpublished internal document, ErosionLab.

