







# **QuickGRASS® PRO MATERIAL SPECIFICATIONS**

#### **Materials:**

Great Lakes Aspen (naturally seed free)
Polypropylene Netting
Stitching Thread
OuickGrass® (dyed green excelsior)

## **Typical Roll Sizes:**

Width:	4.0 ft ( 1.2 m)	2.5 ft ( 0.8 m)
Length:	100.0 ft (30.5 m)	56.3 ft (17.2 m)
Area:	$44.4 \text{ yd}^2 (37.1 \text{ m}^2)$	$16.9 \text{ yd}^2 (14.1 \text{ m}^2)$
Weight:	32.4 lb (14.7 kg)	12.3 lb (5.6 kg)

## **Description:**

QuickGRASS PRO is an erosion control / seed starter blanket that is a stitched excelsior blanket that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. Product shall be Manufactured in the U.S.A.

## **Physical Properties:**

Fiber: Great Lakes Aspen (naturally seed free)

Curled, interlocking fibers with barbed edges

Fiber Size: 80% of fibers a minimum of 6" (15.2 cm) long

 $0.038" \pm 0.008"$  wide x  $0.018" \pm 0.003"$  thick

 $(0.97 \text{ mm} \pm 0.20 \text{ mm wide x } 0.46 \text{ mm} \pm 0.08 \text{ mm thick})$ 

Weight\*:  $0.73 \text{ lb/yd}^2 (0.40 \text{ kg/m}^2) \pm 10\% \text{ @ } 22\% \text{ Moisture}$ Thread Pattern: No more than 4.0" (10.2 cm) transverse stitch spacing Polypropylene (white with UV degrader additive) Net Openings: 1.0" wide x 2.0" long (25.4 mm wide x 50.8 mm long)

Net Configuration: Top side only



<sup>\*</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.









## **MANUFACTURER'S CERTIFICATION**

## **QuickGRASS® PRO – Erosion Control / Seed Starter Blanket**

## **Manufacturer:**

American Excelsior Company – Fiberex<sup>®</sup> Division 4032 Parkway Drive Florence, AL 35630 Toll Free 1-800-243-3455

## **Project Information** (if applicable):

Name:
Location:

**Number:** 

## Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber: Great Lakes Aspen (naturally seed free)

Curled, interlocking fibers with barbed edges

Fiber Size: 80% of fibers a minimum of 6" (15.2 cm) long

 $0.038" \pm 0.008"$  wide x  $0.018" \pm 0.003"$  thick

 $(0.97 \text{ mm} \pm 0.20 \text{ mm wide x } 0.46 \text{ mm} \pm 0.08 \text{ mm thick})$ 

Blanket Length: -0' (m) + 2.0' (0.6 m)Blanket Width: -0'' (mm) + 1.0'' (25.4 mm)

Weight\*:  $0.73 \text{ lb/yd}^2 (0.40 \text{ kg/m}^2) \pm 10\%$  @ 22% Moisture Thread Pattern: No more than 4.0" (10.2 cm) transverse stitch spacing Net Material: Polypropylene (white with UV degrader additive) Net Openings: 1.0" wide x 2.0" long (25.4 mm wide x 50.8 mm long)

Net Configuration: Top side only

Chuck Rayburn – General Manager, Fiberex

Effective Date

**Note:** This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from <a href="www.AmericanExcelsior.com">www.AmericanExcelsior.com</a> at all times.



<sup>\*</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen excelsior is 22%.